

3MP Dome All Time Color Human Traking



FEATURES

- IP PTZ 3 Megapixel
- Support 4G SIM
- Infrared and spotlight adjustable to achieve full color at night
- Support 256GB SD card
- Support Two-way audio
- Support P2P remote monitoring With TrueCloud Application



MP
Camera



Dual
Stream



Digital Noise
Reduction



H.265



Mobile
Surveillance

Technical Specifications

Product Code	T18106
Chipset	GK7205+SC3335
Image Sensor	1/2.7" 3.0MP CMOS SC3335
Resolution	3MP: 2304*1296
Video Compression	H.264/H.265
Lens	F=5.3-96MM
Aperture	F1.6
Zoom	18X Optical Zoom
Video Streaming	Main stream: 2304*1296@15fps, sub stream: 640x360@15fps
IR LED	2pcs ir array led + 4pcs laser array led
White LED	3pcs white light
IR LED Distance	130 Meters
White LED Distance	30 Meters
Min.illumination	Color: 0.001 Lux @ (F1.6, AGC ON), B/W: 0.001 Lux @ (F1.6, AGC ON), 0 Lux with IR
WDR	DWDR
Day & Night	Auto OR Manual; Color / BW/AGC
Noise Reduction	3 DNR
S/N Ratio	≥50dB
Movement Range (Pan)	0°~360°
Movement Range (Tilt)	0°~90° auto flip
Pan Speed	Configurable from 0.01°~60°/S
Tilt Speed	Configurable from 0.01°~30°/S

Preset Points	64 Preset Positions, Precision of Preset Point $\leq \pm 0.1^\circ$
Cruise Scan	3 Sets of Pre-positioned Cruise Routes
Pattern Scan	3 Patterns Scan
Tracking Function	Humanoid Tracking and synchronized zoom
Communication Protocol	PELCO-D/-P adaptive
Baud Rate	57600
Smart Alarm	Humanoid Detection & Motion Detection
Support Protocol	DHCP, DNS, NTP, TCP/IP, HTTP
Communication Interface	Rj45 10-100M, 4G Network
Wireless Standard	4G: LTE-FDD, LTE-TDD
Frequency Band	LTE-FDD: B1/B3/B5/B8, LTE-TDD: B40,
Power	DC12V--3A
Operating Temperature & Humidity	10°C ~ 60°C, less than 90%RH
Power Consumption	Min. 3W (Light off) & Max. 24W (Light on)
Protection Grade	IP 66
Weight Net	02.740KG
Weight Gross	03.720KG

Other Products



Smart Wi-Fi Camera
with Battery T18058



Smart Wall Lamp
T17937



4G Smart All Time Color
Bullet Camera T18075



Motorized Wi-Fi Rotation
Dome Camera T18060



Robot Pan-Tilt
Camera T18061

* Note: Product specifications are subject to change without prior notice.