



Object Left/Lost

Area Detection

Line Crossing

Target Count



- ♦ Intelligent multi-function super starlight warm light full color.
- Smart analysis: Target Count, Object Left /Lost, Area Detection, Line Crossing.
- ICR infrared filter for automatic switching from Day to Night mode and vice versa.
- Supports automatic electronic shutter function to adapt to different monitoring ٥ environments.
- ♦ High-performance 3D digital noise reduction and edge enhancement, using ROI video compression technology, high compression ratio.
- ♦ Support TRUECLOUD PRO APP P2P for mobile phone or computer monitoring.
- Power Input : POE/ DC 12V. ٥
- ♦ Compression: H.265.

Product code	T18081
Image Sensor	1/2.8" IMX307 CMOS sensor
Resolution	1920 x 1080 High Defination
Video Compression	H.264/H.265
·	M12 4mm F1.6 fixed lens
Lens	
IR LED	2 Warm LED
IR Range	20 Meters
Noise Reduction	3D digital noise reduction
WDR	Support WDR ( D-WDR ) > 80db
BLC	Support
S/N Ratio	≥50db (AGC closed )
Minimum Illumination	Color: 0.001Lux@F1.2
Image Settings	Support for brightness, contrast, saturation, white balance, AWB (automatic white balance), AGC (automatic gain), AE (automatic exposure); support privacy area; normal / 90 ° / 270 ° image rotation; Automatic, manual color to black and other switches
OSD	Support
Mirror/Flip	On / Off
Privacy Masking	4 Zone Selectable
Video Main Streaming	1920×1080@1-20 fps
Video Sub Streaming	704×576@1-20 fps & 640×480@1-20 fps
Video Bit Rate	32Kbps-16Mbps adjustable, support CBR / VBR
Audio Streaming	G.711
Audio Bit Rate	64Kbps
Smart Analysis	Target Count, Object Left /Lost, Area Detection, Line Crossing
Protocol	TCP/IP, DHCP, HTTP, HTTPS NTP, DNS, RTP RTSP
User	Support 5 users max
Communication Interface	Rj45 10/100mbps, Analog Audio In
Power Input	POE RJ45 input 48V Standard/DC Input 12V – 2A
Power Consumption	≥3.7W
Operation Temperature/Humidity	-10℃ to +50℃ / 30% to 80% RH
Storage Temperature/Humidity	-20°C to +60°C / 20% to 90% RH
Dimension	97mm(W)x82mm(H)x97mm(L)
Housing type	Plastic Housing
Weight Net	0.187KG
Weight Gross	0.219KG







\* Product housing specifications are subject to change without prior notice.