

Features

- ◆ Support IPC front-end intelligent analysis:
Target Count, Object Left/Lost, Electronic Fence, Line Crossing, Humanoid Detection
- ◆ Supports maximum 4ch sub stream recording synchronous playback
- ◆ Support H.264/H.265/H.265+
- ◆ Support ONVIF, High profile S
- ◆ Support P2P cloud service
- ◆ Instant playback under preview screen without affecting other channel preview
- ◆ Supports disk grouping quotas and disk group storage modes
- ◆ Support channel grouping, preview tour



Product code	T18114
Operating System	Embedded Linux
User Interface	GUI
Video Compression	H.264/H.265/H.265+
Video Resolution	8MP\5MP\3MP\2MP
Smart Features	Target Count, Object Left/Lost, Electronic Fence, Line Crossing, Face Grouping List, Face Detection, Humanoid Detection, Retrograde Detection, Leave Position Detection (need front end IPC supported)
Video Input	4CH Digital (2592X1944) + 4CH Preview + 4CH Playback
HDMI output	1 CH, Resolution : 1024x768/60Hz, 1280x800/60Hz, 1280x1024/60Hz, 1366x768/60Hz, 1440x960/60Hz, 1920x1080/60Hz, 2560x1440/30Hz, 3840x2160/30Hz
VGA output	1 CH, Resolution : 1024x768/60Hz, 1280x800/60Hz, 1280x1024/60Hz, 1366x768/60Hz, 1440x960/60Hz, 1920x1080/60Hz, 2560x1440/30Hz, 3840x2160/30Hz
Decode Playback	4ch At same time Playback
Recording Mode	Timing recording or alarm recording, Timing record, Alarm recorder, Stop record
Playback Mode	On time playback, regular playback, event playback, external file playback, log playback
Backup Mode	Regular backup, event backup, video clip backup
Streaming Type	Audio/Video, Variable Rate(VBR) , Constant Bit Rate(CBR)
Dual stream	Support
Audio Compression	G.711
Network Interface	1, RJ45 10M/100M self-adaptive LAN port
Protocol	DDNS, EMAIL, UPNP, NTP, DHCP, IP Filter, PPPoE, P2P
Network Users	5 User
Network Bandwidth	80Mbps
P2P	Support, Android/Iphone/Windows Pc
Audio Input	IPC composite audio input
Audio Output	HDMI Output
USB Interface	2x USB2.0 rear port
SATA	2 SATA
Capacity	supports MAX 8TB HDD
Working temperature	±10°C---- 55°C
Operating Humidity	10%~90%
Power Supply	DC12V/3.0A
Power Consumption	10W (without HDD)
Dimension	325mm×245mm×55mm
Net Weight	1.2KG
Gross Weight	1.3KG

Technical Data Sheet

