

PRO 3MP Bullet All Time Color Camera



FEATURES

- 24/7 All time color
- 4 mm fixed lens
- Resolution up to 3MP 2304X1296@20fps
- Humanoid detection
- Detection frame 5fps, detect 5 people at the same time
- Support 3D DNR and digital WDR
- Power Input : PoE 48V Standard/ DC 12V
- Compression: H.265/H.264



All-Time Color



PoE



Human Detection



High Resolution



Dual Stream



IP66

Technical Specifications

| | |
|----------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product Code | T18037 |
| Image Sensor | 1/2.9" Low Illumination CMOS Sensor |
| Resolution | 3MP 2304X1296 |
| Video Compression | H.264/H.265 |
| Lens | M12 4mm F1.6 fixed lens |
| Warm LED | 2 Array LED |
| IR Range | 20 Meters |
| Noise Reduction | 3D Digital Noise Reduction |
| WDR | Support WDR (D-WDR) |
| S/N Ratio | ≥50db (AGC closed) |
| Minimum Illumination | Color: 0Lux (Warm light on) |
| Image Settings | Support for brightness, contrast, saturation, white balance, AWB (automatic white balance), AGC (automatic gain), AE (automatic exposure); support privacy area; normal / 90 ° / 270 ° image rotation, Automatic, manual color to black and other switches |
| OSD | Support |
| Mirror/Flip | On / Off |
| Privacy Masking | 4 Zone Selectable |
| Video Main Streaming | 3MP 2304X1296@20fps, 2MP 1920x1080@25fps |
| Video Sub Streaming | D1 (720*576), VGA(640*480), Q720P(640*360) |
| Video Bit Rate | 160Kbps-4000kbps adjustable, support CBR / VBR |

| | |
|--------------------------------|-----------------------------------------------------------------------|
| Audio Streaming | G.711u / 64Kbps |
| Humanoid Detection | ≤5 people |
| Humanoid Size | Humanoid Pixel≥40X40 |
| Humanoid Detection Ratio | ≥99% (meet above requirement) |
| Humanoid Capture Speed | ≤1s |
| Max Humanoid Detection Frame | 5fps/s |
| Humanoid Detection Part | People with any posture including half body, head, hand, shoulder |
| Humanoid Detection method | Support visible light image detection & near infrared image detection |
| Protocol | TCP/IP, DHCP, HTTP, HTTPS NTP, DDNS, RTP RTSP |
| Connection Protocol | ONVIF, T8s, Slink,GB28181 |
| User | Support 3 user max |
| Communication Interface | RJ 45 10/100Mbps, RCA Audio In |
| Power Input | PoE RJ 45 input 48V Standard/DC Input 12V – 1A |
| Power Consumption | ≥3W |
| Operation Temperature/Humidity | -10°C to +50°C / 30% to 80% RH |
| Storage Temperature/Humidity | -20°C to +60°C / 20% to 90% RH |
| Dimension | (H)65 x (W)70 x (D)197 |
| Housing Type | Metal Housing |
| Weight Net | 0.315Kg |
| Weight Gross | 0.385Kg |

*** Note: Product specifications are subject to change without prior notice.**