



Features

- ◆ IP IR Dome 3MP HD
- ◆ 3 Array LED
- ◆ Distance: 20 Meters
- ◆ Power Input : POE 48V Standard/ DC 12V 1Amp
- ◆ Support 2D/3D noise reduction, digital WDR
- ◆ Support ONVIF protocol
- ◆ Compression: H.264/H.265



Product code	T18099-AC
Image Sensor	1/2.8" SC2335 CMOS Sensor
S/N Ratio	> 39.1 dB
Resolution	3MP :2304x1296
Minimum Illumination	Color: 0.1 Lux B/W: 0.01 Lux
Lens	4 MM
IR LED	4A LED
IR Range	20 Meters
OSD	Date Time & Title
White Balance	Auto
Day & Night	Auto / Color / BW
3D-DNR	Auto
Mirror/Flip	On / Off
Privacy Masking	4 Zone Selectable
Video Streaming	Dual Streaming at the Same Time: H.264/H.265; Main stream: 2304x1296@15fps Sub-stream:640x360@15fps
Audio Streaming	G.711 A-Law @ 16bits 8kbps G.711 u-Law @ 16bits 8kbps
Connectors	Rj45 / Analog Audio In
Power Input	POE RJ45 input 48V Standard/DC Input 12V – 1A
Power Consumption	≥5W
Lightning protection	4000V lightning protection
Operation Temperature/Humidity	-10°C to +50°C / 30% to 80% RH
Storage Temperature/Humidity	-20°C to +60°C / 20% to 90% RH
Dimension	109(W)*105(H)
Housing type	Plastic Housing
Weight Net	0.160KG
Weight Gross	0.222KG

Technical Data Sheet



• Product housing specifications are subject to change without prior notice.